

This PUBLIC BILL originated in the LEGISLATIVE ASSEMBLY, and, having this day passed, is now ready for presentation to the LEGISLATIVE COUNCIL for its concurrence.

Legislative Assembly Chamber,
Sydney, 19 December, 1901. }

F. W. WEBB,
Clerk of the Legislative Assembly.

New South Wales.



ANNO PRIMO

EDWARDI VII REGIS.

Act No. , 1901.

An Act to regulate the construction and use of lifts and of scaffolding and engines used for erecting, demolishing, altering, repairing, cleaning, or painting buildings or structures, and of gear used in connection therewith; to regulate the use of steam cranes; and for purposes consequent upon or incidental to those objects.

BE it enacted by the King's Most Excellent Majesty, by and with the advice and consent of the Legislative Council and Legislative Assembly of New South Wales in Parliament assembled, and by the authority of the same, as follows:—

Preliminary.

5 1. This Act shall come into operation on the first day of Commencement and short title.
February, one thousand nine hundred and two, and may be cited as
the "Scaffolding and Lifts Act, 1901."

2. This Act shall have effect in the Metropolitan Police Places within which Act shall operate.
District, and in such other areas as the Governor, by proclamation
10 published in the Gazette, may direct.

Scaffolding and Lifts.

Such district and each such area is referred to in this Act as a district.

3. In this Act—

Definitions.

5 “Engine” means machine, crane, boiler, or other apparatus or contrivance used in erecting, demolishing, altering, repairing, cleaning, or painting buildings or structures.

“Gear” means ladder, chain, rope, fastening, hoist, stay, block, pulley, hanger, sling, brace, or other contrivance.

“Inspector” means inspector appointed under this Act.

10 “Lift” means apparatus or contrivance within a building worked by any power other than hand, and comprising a movable platform by which persons or goods are raised or lowered, and includes any machinery used for working a lift.

15 “Scaffolding” means material, works, or structure set up or built to a height exceeding six feet from the horizontal base on which it is set up or built, for erecting, demolishing, altering, repairing, cleaning, or painting buildings or structures.

20 4. The Governor may, for carrying out the provisions of this Act, appoint inspectors for any districts.

Appointment of inspectors.

Erection of scaffolding.

25 5. (1) No person shall in any district commence to set up or build any scaffolding unless he has stated his intention to do so by notice in writing, under his hand, and served on an inspector for the district by being posted to him or left at such address as the Minister may, by notice in the Gazette, direct, at least twenty-four hours before such scaffolding is commenced to be set up or built.

Notice as to the erection of scaffolding.

30 (2) Any person who commences to set up or build in any district any scaffolding without having notified his intention to do so to the person, in the manner and before the time in this section mentioned, shall be liable to a penalty not exceeding fifty pounds.

Scaffolding, engines, and gear.

35 6. All scaffolding and engines, and all gear used in connection therewith in any district shall be of the description indicated in the regulations in the Schedule hereto, and shall be set up, built, maintained, and used in accordance with such regulations.

Scaffolding, &c, to be in accordance with regulations.

7. The Governor may proclaim regulations annulling, amending, or adding to the regulations in the Schedule hereto.

Governor may by proclamation amend, &c, Schedule.

40 Every proclamation made under this section shall be published in the Gazette and laid before Parliament within fourteen days after such publication, or, if Parliament is not then sitting, within fourteen days after the commencement of the session next ensuing after such publication.

The

Scaffolding and Lifts.

The regulations contained in any such proclamation may be disallowed by resolution of either House of Parliament, in whole or in part, within one month after the proclamation has been laid before that House, and such of the regulations as have not been so disallowed shall, at the end of such period or the last of such periods, have the force of law, and be deemed to be contained in the Schedule hereto.

Construction of lifts.

8. (1) No person shall in a district commence to construct a lift unless he has stated his intention to do so by notice in writing, under his hand, served on an inspector for the district at least twenty-four hours before such lift is commenced to be constructed.

(2) Any person who commences to construct in any district any lift without having notified his intention to do so to the person, in the manner and before the time in this section mentioned, shall be liable to a penalty not exceeding fifty pounds.

Inspection.

9. An inspector shall from time to time inspect all lifts and all scaffolding, engines, and all gear used in connection therewith constructed or used or in course of construction in his district, and for that purpose may during working hours enter any building or premises.

10. (1) Where it appears to an inspector—

- (a) that the use in his district of any lift or any scaffolding or engine or any gear used in connection therewith would be dangerous to human life or limb, or
- (b) that with regard to any scaffolding, engine, or any such gear constructed or used or in course of construction in his district the regulations in the Schedule hereto are not being complied with,

he may give such directions in writing to the owner of or person using such lift or the person in charge or apparently in charge of such scaffolding, engine, or gear as he thinks necessary in order to prevent accidents or to ensure a compliance with such regulations; and such person shall, unless notice of appeal is given as hereinafter provided, forthwith carry out such directions.

(2) Where an inspector gives any directions for any reason mentioned in subsection (a) aforesaid, he may at the same or at any other time order any persons forthwith to cease to use the lift or to work in connection with the scaffolding, engine, or gear until such directions or any order on appeal therefrom has been complied with.

Any such order of an inspector may be rescinded by him.

(3)

Scaffolding and Lifts.

(3) The person to whom such directions have been given, or the owner of the lift or the person in charge of the operations in respect of which the scaffolding, engine, or gear is erected, used, or intended to be used, may, on giving notice to the inspector within 5 twenty-four hours after such directions have been given appeal in person to the Government architect, or any person deputed by the Government architect to hear any such appeal. The said architect or person shall hear and determine such appeal with all reasonable despatch, and shall, by order in writing delivered to the person appealing, affirm, vary, or rescind such directions.

- (4) Any person who—
- (a) refuses or fails to comply with any direction given to him by an inspector in pursuance of this section or any order on appeal therefrom; or
- 15 (b) refuses or fails to comply with any order given to him by an inspector in pursuance of this section to cease to use a lift or to work in connection with any scaffolding, engine, or gear, shall be liable to a penalty not exceeding fifty pounds.

Drivers of steam-cranes.

20 11. (1) No person shall, in any district, act as driver in charge of any steam-crane used in connection with building operations unless he has obtained and holds a driver's certificate. Driver in charge of crane to hold certificate.

A driver's certificate shall be granted by the Government architect to any person who, after inquiry and examination he considers 25 is trustworthy and competent to act as a driver of a steam-crane. Any certificate so granted may be cancelled by the Government architect if he considers that the holder has ceased to be trustworthy or competent as aforesaid.

(2) Any person who, after the expiration of a period of 30 three months from the commencement of this Act, acts in a district as driver in charge of a steam-crane without holding a driver's certificate granted and in force in pursuance of this section, shall be liable to a penalty not exceeding ten pounds. Penalty.

Supplemental.

35 12. Any person who interferes with or obstructs any inspector in the execution of any power or duty conferred or imposed on him by this Act shall be liable to a penalty not exceeding four pounds. Obstruction of inspectors.

40 13. All informations under this Act may be heard and determined, and all penalties may be recovered in a summary way before a court of petty sessions. Recovery of penalties.

Scaffolding and Lifts.

SCHEDULE.

REGULATIONS.

Swinging scaffold.

To bear three times maximum weight required ; blocks to be iron, not less than
5 four inches diameter of sheaf, consisting of double and single block ; and all rope to be
best Manilla, not less than two and three-quarter inches circumference.

Scaffold to consist of two-inch planking running full length, and width to be not
more than eleven feet between supports, such supports to be of wrought-iron two and
one-half inches by one-half inch, carried round stage, with loop on top to receive tackle,
10 and bolted to planking with three-eighths inch bolts each end, strong cleat to be screwed
to planking under centre.

Scaffold to have overhead or wall attachments securely attached.

Guard-rail to be placed three feet from floor, not less than nine inches sectional
area ; also fender board not less than nine inches on front and both ends.

15 *Bricklayers' scaffold.*

Standard to be not more than eight feet apart, consisting of five inches diameter,
or twenty inches sectional area, embedded twelve inches in ground, or in barrels filled
with sand or earth.

Ledgers to be not more than five feet apart, or not less than fifteen inches
20 sectional area.

Putlocks five feet long, and not less than twelve inches sectional area, and should
be of hardwood, split (not sawn), to ensure the length fibres being intact.

Scaffold-boards to be not longer than twelve feet, and not less than one and a
half inch thick, free from all defects. All planking to be laid butting, with two putlocks
25 at each end, and one in centre.

All scaffolds to have twelve inches by one and a half inch fender-board on each
stage, secured to standards ; also guard-rail three feet high, and not less than twelve
inches sectional area on each stage.

Bracing to be not less than twelve inches sectional area, and placed to the satis-
30 faction of the inspector or his representative.

Scaffold to be secured by best Manilla rope, not less than one and three-quarter
inch circumference, and fifteen feet long, or bolts not less than five-eighths inch diameter.
All lashings to be properly wedged, such wedging to be tightened after rain.

Buildings above two stories high, immediately after joist being laid, shall have
35 a temporary covering of close planking on joists or girders, and shall remain until
permanent floors are laid. All gangways to be constructed to the satisfaction of the
inspector.

Internal scaffold—painters, plasterers, general repairs, inclusive.

Ledgers not to be less than fifteen inches sectional area, and not more than six
40 feet apart, with standards not more than six feet apart, and with fifteen inches sectional
area, and braced, as required by inspector, with ropes or bolts, as before mentioned.

Gantries.

Standard to be of not less than eighty-one inches sectional area, and built up of
nine-inch by three-inch Oregon, bolted together with rails, not less than twenty-seven
45 inches sectional area, and cross-braces, not less than twenty-one inches sectional area ;
rails to be not more than eight feet apart. King posts to be not less than one hundred
and forty-four inches sectional area, sole plates not less than eighty-one inches sectional
area.

Truss girders connecting gantry towers. Top and bottom rails to be not less
50 than eighty-one inches sectional area, secured with king rods, not less than one and a
half

Scaffolding and Lifts.

half inch diameter, and cross-bracing not less than twenty-seven inches sectional area, bolted to top and bottom rail, both rails to be strapped to king-posts with three-inch by five-eighths inch straps, four feet long (wrought-iron).

Crane to be properly secured to gantry with wire rope, passed over back legs and 5 sleeper at top, and connected at bottom of each tower, or secured by wrought-iron straps top and bottom of four-inch by three-quarter inch wrought-iron, properly bolted to king-post and crane timbers.

Bolts, three-quarter inch, to be not more than three feet apart, spaced diagonal, and strap to be not less than nine feet long.

10

Lifting capacity.

Any crane must be weighted on each leg to not less than one and a half times its lifting capacity.

Lift-box.

Construction of lift-box to carry up to two tons. To be constructed of one and 15 a half inch thick hardwood, with two bottom ledges six inches by three inches; corner-straps to be six-inch by quarter-inch wrought-iron, bolted through angle of box, carrying straps to pass under ledges on bottom, and carried up sides of box, made of four-inch by five-eighths inch wrought-iron, with eylet-holes thickened to receive box chains, and securely bolted to box with half-inch bolts.

20

Ladders.

All ladders shall be of clean Oregon, with rungs of split hardwood, set in centre of stiles. No batten ladders to be used, other than roof ladders.

All ladders must stand not less than four feet six inches above staging; where the inspector so directs, more than one set of ladders shall be used.

25

All ladders to be effectively lashed and to be stayed where length exceeds twenty-two feet.